



C90

Mobile Computer

- Android 10
- 4G
- WiFi
- Bluetooth
- 1D Barcode
- 2D Barcode
- NFC
- Google Mobile Service
- Camera
- GNSS
- AI Engine

CHAINWAY C90 is our newly-developed, lightweight and portable handheld terminal that exhibits extremely powerful performance. Built with Android 10 OS and high-performance octa-core processor, it features vigorous system configuration. With rich functionality features like outstanding barcode scanning, sturdy WiFi performance, NFC, front and rear cameras, it possesses the best price versus performance ratio. All these make C90 immensely perfect to be implemented in a wide spectrum of industries, including logistics, warehousing, retail, asset tracking etc., assisting customers to improve operation and management levels significantly.



Specification

Physical Characteristics

Dimensions	158.5 x 76.0 x 13.1 mm / 6.24 x 2.99 x 0.52 in.
Weight	230g / 8.11 oz. (device with battery)
Keypad	Power, 2 scan keys, volume +/-
Battery	Main battery: built-in 5000 mAh
	Standby: up to 490 hours (only main battery ; WiFi: up to 470h; 4G: up to 440h)
	Continuous use: over 12 hours (depending on user environment)
	Charging time: 2.5 hours (charge device by standard adaptor and USB cable)
Audio	MIC, receiver, loudspeaker(1W), support voice call
Vibrator	Support
Display	5.7-inch (18:9) , IPS LTPS 1440 x 720
Touch Panel	Corning Gorilla Glass, multi-touch panel, gloves and wet hands supported
Sensor	Proximity sensor, light sensor, accelerometer sensor
Indicator LED	Power, charging, status indicator
Card slot	1 slot for Nano SIM card, 1 slot for Nano SIM or TF card
Interfaces	USB Type-C, USB 2.0, OTG

Performance

CPU	Cortex-A53 2.0 GHz Octa-core
RAM+ROM	3GB + 32GB 4GB + 64GB (optional)
Expansion	Supports up to 128 GB Micro SD card

Developing Environment

Operating System	Android 10 ; GMS, FOTA, SafeUEM supported
SDK	Chainway Software Development Kit
Language	Java
Tool	Eclipse / Android Studio

User Environment

Operating Temp.	-4°F to 122°F / -20°C to 50°C
Storage Temp.	-40°F to 158°F / -40°C to 70°C
Humidity	5% RH - 95% RH non condensing
Drop Specification	Multiple 1.5 m / 4.92 ft. drops to the concrete across the operating temperature range
Tumble Specification	1000 x 0.5 m / 1.64 ft. falls at room temperature
Sealing	IP67 per IEC sealing specifications
ESD	±15 KV air discharge, ±8 KV conductive discharge

Communication

WLAN	Support IEEE802.11 a/b/g/n/ac/d/e/h/i/k/r/v/w, 2.4G/5G dual-band, IPV4, IPV6; Support 5G PA
	Fast roaming: PMKID caching, 802.11r, OKC
	Operating Channels: 2.4G(channel 1~13), 5G(channel 36,38,40,42,44,46,48,52,56,60,64,100,104,108,112,116,120,124,128,132,136,140,149,153,157,161,165), depends on local regulations
	Security and Encryption: WEP, WPA/WPA2-PSK(TKIP and AES), WAPI-PSK—EAP-TTLS, EAP-TLS, PEAP-MSCHAPv2, PEAP-LTS, PEAP-GTC, etc.
WWAN(Europe/Asia)	2G: GSM850/GSM900/DCS1800/PCS1900
	3G: CDMA EVDO: BC0
	WCDMA: B1/B2/B4/B5/B8 TD-SCDMA: A/F(B34/B39)
WWAN(America)	4G: B1/B2/B3/B4/B5/B7/B8/B20/B34/B38/B39/B40/B41
	2G: GSM850/GSM900/DCS1800/PCS1900
	3G: CDMA EVDO: BC0/BC1
	WCDMA: B2/B4/B5/B8 4G: B2/B4/B5/B7/B8/B12/B17/B28A/B28B/B38
Bluetooth	V2.1+EDR, 3.0+HS and V4.1+HS, BT5.0
GNSS	GPS/AGPS, GLONASS, BeiDou, Galileo, internal antenna

Data Collection

Camera

Front Camera	5MP
Rear Camera	Rear 16MP Autofocus with flash

NFC

Frequency	13.56 MHz
Protocol	ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc.
Chips	M1 card (S50, S70), CPU card, NFC tags, etc.
Range	2-4 cm

Barcode Scanning (optional)

2D Scanner	Honeywell: N6603 / N6703
1D Symbologies	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.
2D Symbologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), etc.

Optional accessories (See details in Accessory Guide)

Charging Cradle; Lanyard etc.

Notice: Product specifications are subject to change without prior notice. / Model: C90 / Update Date: 2021-01-12

CHAINWAY®

Shenzhen Chainway Information Technology Co., Ltd

Address: 9F, Building2, Phase 2, Gaoxinqi Industrial Park, Liuxian 1st Rd., Bao'an District, Shenzhen, Guangdong 518102, China

Tel: 0086-755-23223316

Fax: 0086-755-23223310

Email: sales@chainway.cn

Web: http://www.chainway.net